

Auto G 14 D2

High Performance Long Term Grease



YOUR BENEFITS

- Provides good water resistance.
- Extended re-lubrication period.
- Excellent mechanical stability.
- Guards against rust & corrosion.
- Minimizes wear.
- Withstands heavy loads.
- Does not contain lead or other harmful metals.

APPLICATION

- For reliable usage in auto components like door & boot latches, hinges & window regulators.
- For long term lubrication on seat slider mechanism.
- For applications in automotive industry for in-car use.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth / Off White
Colour	Visual	-	Beige to Light Yellow
Base [Thickener]	-	-	Lithium - Calcium
Base Oil	-	-	Mineral
Base Oil Viscosity @40°C	ASTM D 445	cSt	120
Flash Point (of Base Oil) [min]	ASTM D 92	°C	230
NLGI Grade	-	-	# 2
Worked Penetration @25°C	ASTM D 217	0.1 mm	265 - 295
Dropping Point	ASTM D 2265	°C	+180
Water Washout @80°C, wt. loss	ASTM D 1264	%	< 5
Four Ball Weld Load	ASTM D 2596	Kgs	250
Oil Separation @100°C / 24 Hrs	ASTM D 6184	%	< 3
Copper Strip Corrosion Test	ASTM D 4048	Rating	1a
Operating Temperature Range	-	°C	-30 / +140

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

INDUSTRY:

Automotive

PACK SIZE:

20 kg Bucket
180 kg Drum

SHELF LIFE:

24 Months

