

Auto G 35 MV 2 F

Synthetic grease for Plastic to Plastic Components & Precision Bearings



YOUR BENEFITS

- Long life lubrication.
- Most suited for plastic to plastic, plastic to metal & metal to metal substrates.
- For moderate movements and light loads.
- Compatible with most plastics and elastomers due to chosen PAO oil blend.
- Contains pulverised PTFE.
- Very low co-efficient of friction.
- Guards against corrosion.
- Chosen additives to give maximum performance.

APPLICATION

- Auto ancillaries, window regulators, door locking, central locking systems, sunroofs.
- Automobile ancillaries.
- For timers, track-rod joints.
- For lubrication of plastic to plastic, metal to metal to plastic combination components under moderate speeds and light loads.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance / Colour	Visual	-	Smooth / Beige
Base / Base Oil	-	-	Lithium / Polyalphaolefin
Base Oil Viscosity @40°C	ASTM D 445	cSt	30-35
Base Oil Viscosity @100°C	ASTM D 445	cSt	5 - 7
NLGI Grade	-	-	#2
Worked Penetration @25 °C	ASTM D 217	0.1 mm	265 - 295
Dropping Point	ASTM D 2265	°C	>=190
Evaporation Loss 24 Hrs @100°C	ASTM D 972	%	2 max
Oil Separation 24 Hrs @100°C	ASTM D 6184	%	5 max
Copper Strip Corrosion Test	ASTM D 4048	Rating	1a (No Corrosion)
Operating Temperature Range	-	°C	-50/+140

INDUSTRY:

Automotive

PACK SIZE:

20 kg Bucket
180 kg Drum

SHELF LIFE:

24 Months

CTM:-Corporate Test Method

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

