

Auto G SR 14 D2

Multi-Purpose Automotive Grease For Sliding Assemblies



YOUR BENEFITS

- Outstanding Metal to Metal Lubrication.
- Reduces friction and wear and provides excellent sliding performance.
- Excellent low temperature performance.
- Has very good resistance to oxidation, corrosion and water washout.

APPLICATION

- For automotive seat sliding assemblies.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	Yellowish
Base [Thickener]	-	-	Special Soap
Base Oil	-	-	Mineral
Base Oil Viscosity @40°C	ASTM D 445	cSt	100
NLGI Grade	-	-	#2
Worked Penetration @25°C	ASTM D 217	0.1 mm	265 - 295
Dropping Point	ASTM D 2265	°C	190
Copper Strip Corrosion Test	ASTM D 4048	Rating	1a
Bearing Corrosion Test	ASTM D 1743	-	Pass
Operating Temperature Range	-	°C	- 20 / +120

INDUSTRY:
Automotive

PACK SIZE:
20 kg Bucket
180 kg Drum

SHELF LIFE:
24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.