

AutoDamp 15 J 00 FX

PTFE fortified Synthetic Grease



YOUR BENEFITS

- ✔ Very Low friction synthetic grease
- ✔ Reduced effort, Low noise, improved efficiency in applications
- ✔ Suitable for plastic-plastic and metal-plastic pairings.
- ✔ Wide operating temperature band.
- ✔ Compatible with most plastics.

APPLICATION

- ✔ Applications include gear shifters, latches, control cables etc.
- ✔ Offers excellent dampening properties, low noise and high efficiency.
- ✔ Finds use also in industrial machinery and domestic & kitchen appliances.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	White
Base [Thickener]	-	-	Lithium Soap
Base Oil	-	-	Silicone
Base Oil Viscosity @25°C	ASTM D 4878	cSt	500
NLGI Grade	-	-	#00
Worked Penetration	ASTM D 217	0.1 mm	400-430
Dropping Point	ASTM D 2265	°C	>300
Operating Temperature Range	-	°C	-60 to +200

INDUSTRY:
Automotive

PACK SIZE:
20 kg Bucket
180 kg Drum

SHELF LIFE:
24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

