

BRB 30

High Performance EP Moly Grease For Medium Loads



YOUR BENEFITS

- Withstands extreme pressure and high loads.
- Good shear stability.
- Reduces friction and wear and thereby minimizes maintenance costs.
- Provides adequate rust protection to bearing surfaces.
- Extends re-lubrication cycle as MoS₂ provides solid lubricating film.
- Wide range operating temperature band.
- Good resistance to oxidation and hot & cold water.

APPLICATION

- For all types of anti-friction, plain / bush / sleeve bearings.
- Universal joints, splined shafts, springs and sliding mechanism.
- Lubrication of chains on motor vehicles, trucks, transportation equipment and material handling systems.
- Cables in Steel Mills.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	Black
Base [Thickener]	-	-	Lithium
Base Oil	-	-	Mineral
Base Oil Viscosity at 40°C	ASTM D 445	cSt	120
NLGI Grade	-	-	# 2
Worked Penetration	ASTM D 217	0.1 mm	265 - 295
Dropping Point	ASTM D 2265	°C	+180
Four Ball Weld Load	ASTM D 2596	Kgs	250
Four Ball Wear Scar	ASTM D 2266	mm	0.8
Operating Temperature Range	-	°C	-20/+150

INDUSTRY:

Automotive Components,
Sugar

PACK SIZE:

1 kg / 5 kg / 20 kg Bucket
180 kg Drum

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.