

DR Grease HD 1

Highly Water Resistant & Temperature Resistant Drill Rod Grease



YOUR BENEFITS

- Designed for core drillers to extend the life of not only the rod but head as well.
- Stops vibration in the bore hole, which will lead to longer thread life, cuts down on the wear and tear of the drill head.
- Resists corrosion, wear and oxidation.
- Tackiness assures adherence to drill rods while providing superior resistance to water washing centrifugal separation.
- Prevents chattering of the rods.

APPLICATION

- Recommended for lubrication on diamond drill rods operating on surface or underground.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth & Tacky
Colour	Visual	-	Red
Base Oil Viscosity @40°C	ASTM D 445	cSt	650
NLGI Grade	-	-	# 1
Worked Penetration	ASTM D 217	0.1 mm	310 – 340
Dropping Point	ASTM D 2265	°C	+ 300
Four Ball Wear Scar	ASTM D 2265	mm	0.92
Four Ball Weld Load	ASTM D 2596	Kg	400

INDUSTRY:

Mining

PACK SIZE:

180 kg Drum

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

