

Ecokleen Plus

Water Based Eco friendly Cleaner and Degreaser

YOUR BENEFITS

- Superior Cleaning ability, ecofriendly nontoxic and bio degradable.
- Free from chlorinated or petroleum solvents and ozone depleting substances.
- Phosphate, butyl and caustic free.
- Highly economical non-inflammable heavy duty cleaner and degreaser.
- Contains special corrosion inhibitor to provide adequate rust protection to components.
- Ideal choice for surface cleaning replacing conventional diesel, kerosene or solvent wiping.

APPLICATION

- Auto components, bearings, castings, dies, forgings, machinery, moulds, pipes, pistons, shafts, tools, tanks and vessels.
- Concrete and Asphalt floors, wood, plastics and glass.
- For cleaning applications in all types of industrial, oilfield, mining, marine, hotels, hospitals, commercial and domestic and many others.
- pH value to be maintained in between 8 to 9.5 for good cleaning and to avoid rust.

SUBSTANCES REMOVED

- Grease, oil, grime, dirt, hydrocarbon deposits, wax, soot, stamping, drawing and cutting fluids, animal fat, lubricants, light carbon, tar, food stains and others.

METHOD OF APPLICATIONS

- Dilute Ecokleen Plus with water (up to 50 ppm).
- Can be applied by brushing or spraying and may be used in dip tanks, power washers, steam cleaners, ultrasonic cleaners etc.
- Dilution levels will vary depending on degree of contamination present on the surface.

Ecokleen Plus

Water Based Eco friendly Cleaner and Degreaser



RECOMMENDED DILUTION RATIO:

- Heavy Duty cleaning & degreasing – Dilute 1 part of Ecokleen Plus to 10 parts of water.
- Normal cleaning & degreasing – Dilute 1 part of Ecokleen Plus with 25 - 50 parts of water.

STORAGE

- Store in cool dry place away from direct heat or sunlight.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Clear Liquid
Colour	Visual	-	Pinkish
Density @29.5°C	ASTM D 1298	gms/cc	1.0 -1.1
pH Value	CTM*	-	9.5 - 10.5

CTM:-Corporate Test Method

The values quoted above are typical and do not constitute a specification.

INDUSTRY:

MRO

PACK SIZE:

30 Ltr.

SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.