

## Ecosil NS

Non Silicone Base Mould Release Spray



### YOUR BENEFITS

- Excellent penetration in hard to reach areas.
- Non-staining and non-corrosive.
- Especially formulated as a mould release for parts which are required to be painted.
- No peel off of paint.
- Improved finish.
- Low down time provides increased productivity.
- Ozone friendly propellant promotes clean environment.

### APPLICATION

- As a mould release agent for plastic components which are required to be painted.
- As an antisplatter for metal surface which require post weld painting.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Colour	Visual	-	Pale Yellow
Density @ 29.5°C	*CTM	gms/cc	1.4±0.1
Propellant	-	-	Non CFC

\*CTM=Corporate Test Method

The values quoted above are typical and do not constitute a specification.

Carton size : 25 cans per carton

#### INDUSTRY:

Plastic Moulding

#### PACK SIZE:

550 ML

#### SHELF LIFE:

18 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

