

# Graphol GFL Ultra 300

*New Generation Graphite Based Hot Forging Lubricant*



## DESCRIPTION

- Graphol GFL Ultra 300 is a high performance forging lubricant with an ultrafine mean graphite particle size. Best in class performance provides efficient die wetting and good die life.

## YOUR BENEFITS

- Low build up on the dies or tool wear.
- Extended Die Life.
- Good release and lubricity.
- Excellent coverage of tools over a wide range of temperature.
- Nonflammable & Non Corrosion protection.
- No Sedimentation, Stability of concentrate during storage.

## APPLICATION

- Hot forging of gear and transmission assembly.
- Hot forging of crankshaft, connecting rods, pinion assemblies.
- Forging of rocker arms, ball joints.
- Precision forging of small crankshaft assemblies.

## METHOD OF APPLICATIONS:

- Sprays.
- Hand held spray gun.
- Fixed auto spray system.
- Pumping / Flooding.
- Pre-coating.

## Graphol GFL Ultra 300

New Generation Graphite Based Hot Forging Lubricant



### RECOMMENDED DILUTION RATIO:

- The recommended dilution ratio depends on the difficulty of job and the cooling the equipment. For Initial trial ratio of one part product to ten parts water (1:10 to 1:15) by volume.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	CTM 162	–	Smooth
Color	CTM 162	–	Greyish Black
Solid lubricant	–	–	Graphite
Carrier/diluent	–	–	Water
Density @29.5°C	CTM 069	gms/ml	1.0 – 1.20
pH Value	ASTM D 1287	–	10 – 12
Solid Content (120°C for 2 Hrs)	CTM 033	%	26 - 30
Particle Size of Graphite	–	microns	≤ 3.0

### INDUSTRY:

Forging

### PACK SIZE:

50 kg / 200 kg

### SHELF LIFE:

12 Months

\*CTM: - Corporate Test Method

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

