

## HVG 28/6

High Performance Silicone Grease



### YOUR BENEFITS

- Tacky grease designed for specific applications.
- Non toxic.
- Offers good resistance to solvents like Methanol, Isopropanol, Acetone, Methyl Ethyl Ketone, Diethylene Glycol, Ethanol and hot and cold water.
- Does not affect plastic or rubber parts.
- Strong adhesive sealant.
- Non melting.
- Stable over wide range temperature band of (-) 40°C to (+) 260°C.

### APPLICATION

- For lubrication of valves used in chemical industry and hot and cold water lines.
- Designed for sanitary fittings.
- As a lubricant for plastic and rubber parts.
- For lubrication and protection of O-rings, rubber seals and other rubber assemblies.
- For pneumatic equipments.
- For food industries.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth, Tacky
Colour	Visual	-	Translucent White
Base [Thickener]	-	-	Non Soap
Base Oil	-	-	Silicone
NLGI Grade	-	-	# 2 / 1
Worked Penetration	ASTM D 217	0.1 mm	300 – 320
Dropping Point	ASTM D 2265	°C	None
Oil Separation @ 100°C, 24 hrs	*CTM	%	< 2
Operating Temperature Range	-	°C	-40/+260

CTM: - Corporate Test Method

The values quoted above are typical and do not constitute a specification.

#### INDUSTRY:

MRO

#### PACK SIZE:

1 Kg / 5 Kg / 20 kg Bucket

#### SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

