

## Neverust 20

Heavy Duty Corrosion Protector



### YOUR BENEFITS

- Displaces moisture.
- Forms a thick oily non-drying film giving complete protection to expensive components.
- Long term protection from rust and corrosion due to sea water and rain water.
- Formulate with specialty VCI additives for providing corrosion inhibition to difficult-to-reach areas.
- Provides both superior lubrication and heavy duty corrosion inhibition to metal parts and assemblies upto a period of 2 years if stored indoors.
- Protects equipment parts and spares during storage, shipment and in process.
- Can be easily removed by alkaline cleaners or degreasing solvents. Recommended Moly-Graph® U-Kleen for effective removal.
- Product free from nitrites, chromates or other heavy metals.
- Eco friendly propellant.

### APPLICATION

- Protective coating for assemblies during shipment, indoor and outdoor storage.
- Protects steel, cast iron, zinc, brass, aluminum etc.
- As a protector cum lubricant for stored machinery, cutting tools, engine blocks, pistons, guides, chains, bearings and wire ropes, exposed to sea water.

### METHOD OF USE:

- For effective spraying shake the Can vigorously for at least a minute before use.
- Spray from a distance of 6" to 8" inches from the object.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Colour	Visual	-	Clear / Green
Density @ 29.5°C	*CTM	gms/cc	0.85±0.05
Film Appearance	-	-	Non-drying adherent oily
Average Film Thickness	*CTM	μ	20 – 30
Salt Spray Corrosion Test (passes)	ASTM B 117	Hrs	≥ 200
Propellant	-	-	Non CFC

\*CTM=Corporate Test Method

The values quoted above are typical and do not constitute a specification.

Carton Size : 25 cans per carton

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

#### INDUSTRY:

MRO, Plastic Moulding

#### PACK SIZE:

500 ML

#### SHELF LIFE:

18 Months

