

Neverust 30

Dry Waxy Film Corrosion Protector



YOUR BENEFITS

- A long term indoor / outdoor corrosion inhibitor.
- Waxy film seals out moisture completely.
- 7 Non-reactive to rubber, plastic or painted surfaces.
- 7 Long term protection (upto 1 year indoor) for all metals during shipment or extended storage.
- 7 Can be easily removed with common cleanser solvents.
- → Ozone friendly propellant promotes clean environment.

APPLICATION

- Machined surfaces and assemblies subject to long periods of storage or adverse shipping conditions.
- Equipment's storage, cable and sealer, valves, pipe fittings, long term spare parts storage, armature storage, dies, moulds, cutting tools, motors, shafts.
- 7 Protection of all equipment subject to heat, humidity, chemicals or severe corrosive atmospheres.

METHOD OF USE:

- Shake can well before use.
- 7 The surface to be treated should be thoroughly cleaned, degreased and dried before application.
- 7 For best result keep the Aerosol Can 8" to 10" away form the job at the time of spraying.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Colour	Visual	-	Light Blue
Density @ 29.5°C	*CTM	gms/cc	0.70±0.10
Film Type	Visual	-	Dry Waxy
Average Film Thickness	*CTM	μ	3 – 4
Drying Time			
Touch Dry	Visual	Minutes	10
Tack Free	Visual	Minutes	30
Salt Spray Corrosion Test (passes)	ASTM B 117	Hrs.	≥150
Propellant	-	-	Non-CFC

INDUSTRY:

MRO

PACK SIZE:

500 MI

SHELF LIFE:

18 Months

The values quoted above are typical and do not constitute a specification.

Carton Size : 25 cans per carton.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WAR RANTIES OF EVERY KIND AND NATURE.



W:www.molygraph.com E:sales@molygraph.com M:+918104409925

Page 1 Edition 13.05.19



^{*}CTM=Corporate Test Method