

Prime Paste RNG 250

Prime paste for running-in of gears



YOUR BENEFITS

- Provides excellent protection against corrosion.
- Reduces friction and wear and thereby minimizes maintenance costs.
- Allows control of the gears alignment
- Extends re-lubrication cycle as ${\rm MoS}_{\scriptscriptstyle 2}$ provides solid lubricating film.
- Creates excellent conditions for the running-in of gears
- Avoids seizing
- Does not contain bitumen, solvent, lead or other heavy metals.

APPLICATION

- 7 Running-in and repair of gears found in cement industries, mining etc
- Assembly of shafts/anti-friction
- Universal joints, splined shafts, springs and sliding mechanism.
- Molygraph Prime Paste RNG-250 must be rubbed in with a rotary hand tool, a hard brush or a leather cloth. To achieve a perfect adhesion of the lubricants film on the metallic surface, thorough cleaning with a solvent is recommended.
- 7 For gears, when performing a first running-in with the paste, it is recommended to use the running in grease MOLYGRAPH® Spray Lube 1250 RNG as an open gear grease in order to complete the creation of a solid lubrication film on the surface.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth Paste
Colour	Visual	-	Greyish Black
Base Oil	-	-	Mineral
NLGI Grade	-	-	# 2/3
Worked Penetration	ASTM D 217	0.1 mm	250 - 270
Solid Lubricant	-	-	MoS ₂

The values quoted above are typical and do not constitute a specification.

INDUSTRY:

Steel

PACK SIZE:

180 kg Drum

SHELF LIFE:


24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WAR RANTIES OF EVERY KIND AND NATURE.



W:www.molygraph.com E:sales@molygraph.com M:+91 81044 09925

Edition 13.05.19

