

## SC 2000

Thread Pipe Storage Compound



### YOUR BENEFITS

- Long term storage compound designed to protect all types of threaded surfaces.
- Adheres to metal.
- Excessive circumferential is prevented by increasing the coefficient of friction under compressive forces.
- EP additives provide protection against galling and seizing and help in easy breakout.
- Protects against rust & corrosion.
- Excellent frictional characteristics help to tighten the connections at desired stress levels.

### APPLICATION

- A protective grease-like coating to protect equipment and threaded pipe ends against rust and corrosion.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	Off White
Thickener	-	-	Complex
Fluid Type	-	-	Petroleum
NLGI Grade	-	-	0.5
Worked penetration	ASTM D 217	0.1 mm	330 – 350
Flash Point	ASTM D 92	°C	>200
Density	CTM*	Gms/cc	1.20 ± 0.05
Copper Strip Corrosion	ASTM D 4048	Rating	1a

#### INDUSTRY:

Oil & Gas

#### PACK SIZE:

20 kg / 25 kg Bucket

#### SHELF LIFE:

24 Months

\*CTM = Corporate Test Method

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

