

SmoothSlide 68 D

Premium Quality Machine Tool Slideway Lubricants



YOUR BENEFITS

- Formulated with highly refined based stocks.
- Balanced with advance additives to enhance tackiness & meet the lubrication demands of present day machine tools.
- Excellent low frictional properties.
- Good slide way adhesion & hence give stain free machining.
- Excellent oxidation & anti-corrosion performance.
- Exhibit good anti wear & stick slip characteristics.
- Improved emulsion separation performance & thus resists wash out by coolants.

APPLICATION

- Machine tool slide ways, tables & feed mechanism.
- All machine tool parts including bearings & gear boxes lubricated by circulating systems.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Clear
Colour	Visual	-	Light Amber
Density @ 29.5°C	*CTM	gms/cc	0.85 ± 0.05
Viscosity @ 40°C	ASTM D 445	cSt	60-76
Flash Point [Min]	ASTM D 92	°C	>220
Four Ball Weld Load	ASTM D 2596	Kgs	200
Pour Point	ASTM D 97	°C	-10
Copper Strip Corrosion	ASTM D 130	Rating	1b or better

*CTM=Corporate Test Method

The values quoted above are typical and do not constitute a specification.

INDUSTRY:

Metal Cutting
& Forming

PACK SIZE:

30 Ltr. Bucket
210 Ltr. Drum

SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

