

# Stenol 200 ST (N)

High Performance High Temperature Stenter Chain Oil



## YOUR BENEFITS

- Extremely low evaporation rate at 250°C ensures providing prolonged lubrication to chains operating at higher temperature. Hence further reduces wear & tear.
- Being synthetic oil the chain remains clean due to low residue formation and carbonization.
- Oil does not drip and soil the parts even at high operating temperatures of (+)250°C.

## APPLICATION

- Stenter frame ovens.
- Conveyor Chains operating under heavy loads and high temperatures.
- Chains under moist atmospheres in glassworks, rolling mills and foundries.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Clear
Colour	Visual	-	Colourless
Base Oil	-	-	Synthetic
Density @ 29.5°C	ASTM D 1298	g/cc	0.920
Viscosity @ 40°C	ASTM D 445	cSt	200
Viscosity @ 100°C	ASTM D 445	cSt	20.5
Viscosity Index	ASTM D 2270	-	115
Flash Point [min.]	ASTM D 92	°C	270
Operating Temperature	-	°C	Up to 250

*The values quoted above are typical and do not constitute a specification.*

### INDUSTRY:

Textile

### PACK SIZE:

5 kg / 30 Kg Bucket  
210 kg Drum

### SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

