

## Super Grease EP Series

Premium Quality EP Grease



### YOUR BENEFITS

- High load carrying capacity.
- Protects equipment's from excessive wear.
- Protects against rust and corrosion.
- Adequate lubrication over extended intervals.

### APPLICATION

- Plain and Auto-friction bearings in automotive, earth moving equipment's, gear couplings, electricmotors, wiring equipment's and general machinery.

| CHARACTERISTICS             | TEST METHOD | UNIT   | EP 2         | EP 1         | EP 0         | EP 00        | EP 000       |
|-----------------------------|-------------|--------|--------------|--------------|--------------|--------------|--------------|
| Appearance                  | Visual      | –      | Smooth       | Smooth       | Smooth       | Smooth       | Smooth       |
| Colour                      | Visual      | –      | Yellowish    | Yellowish    | Yellowish    | Yellowish    | Yellowish    |
| Base [Thickener]            | –           | –      | Special Soap | Special Soap | Special Soap | Special Soap | Special Soap |
| Base Oil Viscosity @40°C    | ASTM D 445  | cSt    | 100          | 100          | 100          | 100          | 100          |
| NLGI Grade                  |             | –      | #2           | #1           | #0           | #00          | #000         |
| Unworked Penetration @25°C  | ASTM D 217  | 0.1 mm | 265 - 295    | 310 – 340    | 355 - 385    | 400 - 430    | 445 - 475    |
| Worked Penetration @25°C    | ASTM D 217  | 0.1 mm | 265 - 295    | 310 – 340    | NA           | NA           | NA           |
| Dropping Point              | ASTM D 2265 | °C     | 180          | 180          | NA           | NA           | NA           |
| Four Ball Weld Load         | ASTM D 2596 | Kgs    | 250          | 250          | 250          | 250          | 250          |
| Operating Temperature Range | –           | °C     | -20/+120     | -20/+120     | -20/+120     | -20/+120     | -20/+120     |

#### INDUSTRY:

MRO

#### PACK SIZE:

20 Kg Bucket  
180 Kg Drum

#### SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WAR RANTIES OF EVERY KIND AND NATURE.

