

## Ultra Mill Grease CS HT

*Long life Premium Grade High Temperature Grease*



### YOUR BENEFITS

- ✔ Excellent resistance to water washout.
- ✔ Good resistance to coolants even in mild acidic conditions.
- ✔ Withstands high loads and extreme pressures.
- ✔ Provides good protection against rust and corrosion.
- ✔ Tacky nature provides good adherence to metal substrates.
- ✔ Withstands high temperatures.
- ✔ Wide range operating temperature band of (-) 20 to (+) 200°C.
- ✔ Good pumpability.
- ✔ Fortified with chosen anti-wear and anti-corrosion additives.
- ✔ Extends bearing lives.

### APPLICATION

- ✔ Ideally suited for cold Rolling mills / Paper mills.
- ✔ For medium to slow moving heavily loaded work roll & back up roll bearings, universal joint crosses.
- ✔ For heavy duty applications in agriculture, steel, rubber mills, paper mills, cement, chemical and many other industries

# Ultra Mill Grease CS HT

Long life Premium Grade High Temperature Grease



CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	Light Brown
Base [Thickener]	-	-	Calcium Sulphonate Complex
Base Oil	-	-	Mineral
Base Oil Viscosity @ 40°C	ASTM D 445	cSt	460
Flash Point (of Base Oil)	ASTM D 92	°C	300
NLGI Grade	-	-	# 2
Worked Penetration	ASTM D 217	0.1 mm	265 – 295
Dropping Point	ASTM D 2265	°C	+3000
Four Ball Welded Load	ASTM D 2596	Kgs	500
Water Resistance	ASTM D 1264	%	< 1.5
Copper Strip Corrosion Test	ASTM D 4048	Rating	1a
Operating Temperature Range	-	°C	-20/+200

The values quoted above are typical and do not constitute a specification.

## INDUSTRY:

Steel

## PACK SIZE:

20 kg Bucket

180 kg Drum

## SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

