

Ultratack Mill Grease 700 EP

Heavy Duty High Load High Temperature Long Life Bearing Grease



YOUR BENEFITS

- Designed for maximum wear protection
- High load carrying capacity.
- Excellent work stability good pumpability.
- Withstands temperature as high as (+) 150°C.
- Good adherence to base metal due to high base oil viscosity.
- Offers very good corrosion protection.
- The metal complex provides high-temperature stability.
- Extended re-lubrication period.

APPLICATION

- Multipurpose bearing grease suitable for high and low speed, high load bearing.
- Specially formulated for Rolling Mill (Steel and Paper)

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth
Colour	Visual	-	Greenish to brown
Base (Thickener)	-	-	Lithium
Base Oil	-	-	Mineral
Base Oil Viscosity @ 40°C	ASTM D 445	cSt	400
Flash Point (of Base Oil)	ASTM D 92	°C	200
NLGI Grade	-	-	#2
Worked Penetration @ 25°C	ASTM D 217	0.1 mm	265 – 295
Four Ball Weld Load	ASTM D 2596	Kgs	200
Dropping Point	ASTM D 2265	°C	+190
Operating Temperature Range	-	°C	-20/+150

INDUSTRY:

Steel

PACK SIZE:

180 Kg Drum

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

