

VLG 620

Inert valve grease for oil and gas applications



YOUR BENEFITS

- Extended preventative maintenance periods.
- Hydrocarbon, H₂S resistant.
- Provides superior sealing properties without hardening.
- Cohesive and adhesive.
- Water resistant.
- Rust, Corrosion and oxidation preventive.
- Non-hazardous.
- Non-melting and stable.
- Does not contain volatile solvents.

APPLICATION

- Gate valves, wellheads, pipeline valves, or any area where resistance to hydrocarbons is required.

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Smooth, adhesive
Colour	Visual	-	Black/Gray
Thickener	-	-	Inorganic thickener
Base Oil	-	-	Synthetic
Specific gravity	CTM*	gms/cc	1.25
NLGI Grade	-	-	# 2
Worked penetration	ASTM D-217	0.1 mm	265 – 295
Dropping point	ASTM D-2265	°C	None
Weld load	ASTM D 2596	Kgs	>620
Copper strip corrosion	ASTM D 4048	Rating	1a
Hexane, Petrol and Diesel resistance	-	-	Excellent
H ₂ S, HCL and CO ₂ resistance	-	-	Excellent

*CTM=Corporate Test Method

The values quoted above are typical and do not constitute a specification.

INDUSTRY:

Oil & Gas

PACK SIZE:

5 Kg / 18 Kg Bucket

SHELF LIFE:

24 Months

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product.

MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

