

WIREFLO 350

High-Temperature Wireline Grease Seal

YOUR BENEFITS

- High viscosity index helps in retaining the viscosity at wide temperatures.
- Reduces friction and wear of wireline.
- Excellent adhesion to wireline reducing dripping during operations.
- Wireflo 350 retains higher working pressure using less product.
- Protects wireline against Corrosive effect of H₂S, CO₂ and other down hole chemicals.

APPLICATION

- Wireline operations

CHARACTERISTICS	TEST METHOD	UNIT	TECHNICAL VALUES
Appearance	Visual	-	Tacky Viscous Liquid
Colour	Visual	-	Yellow, Honey-like
Density @ 29.5°C	ASTM D 1298	Gms/cc	0.80 - 0.90
Viscosity @ 100°C	ASTM D 445	cSt	1200 – 1400
Copper Strip Corrosion Test	ASTM D 130	Rating	1b or Better
Corrosion Preventive Test	ASTM D 1743	-	Pass
Rust Preventive Characteristics	ASTM D 665 B	-	Pass
Flash Point [Min.]	ASTM D 92	°C	200

INDUSTRY:

Oil & Gas

PACK SIZE:

30 Ltrs. Bucket
200 Ltrs. Drum

SHELF LIFE:

24 Months

The values quoted above are typical and do not constitute a specification.

Marginal variation in shade can be expected from batch to batch. The color has no effect on the lubricating properties of the product. MSDS available on request. Due to continual upgradation of products above data is subject to change without notice.

This supersedes our previously issued data sheets.

Information and data given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of a product for a particular use is beyond our control; all risks of use of the product are assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE.

